

SPECIFICATIONS		1999 SALEEN S351	
GENERAL	Coupe	Convertible	
Curb Weight, lb.	3064+ Saleen	3203+ Saleen	
Weight Distribution, F/R	56/44		
Fuel Capacity, gal.	15.7		
Wheelbase, in.	101.3		
Track, F/R	59.7/61.5		
Width	73.1		
Length	183.2		
Height	52		
Trunk Space, cubic ft.	10.9	7.7	

ENGINE

Type	High Output, OHV 90 Degree V8		
Bore and Stroke	4.00 x 3.50 in.		
Displacement	5.8L, 351 c.i.d.		
Compression Ratio	8.2:1		
Induction System	Sequential electronic fuel-injection, 65 mm throttle body, Saleen Upper/Lower manifold, 80 mm mass-air sensor, 36 lb./hr fuel injectors		
Camshaft	Hydraulic Roller Camshaft and Lifters		
Pistons	Forged Aluminum		
Exhaust System	Saleen Ceramic Coated Headers, Stainless 2.5 in. 4-way Catalytic High Flow Exhaust		
Horsepower	495 hp @ 5400 RPM		
Torque	490 ft.-lbs. @ 3500 RPM		
Fuel	Premium Unleaded 92 Octane		
Supercharger, Saleen	Standard (Centrifugal)		

DRIVETRAIN

Transmission	6 Speed Transmission		
8.8 in. Differential 3.27 Ratio	Standard		
8.8 in. Differential 3.55 Ratio	Optional		
Saleen Traction Control System	Optional		

SUSPENSION

Front	Hybrid Macpherson strut with Saleen N2 struts and variable rate springs mounted on lower control arms. 1.38 in. stabilizer bar with urethane pivot bushing. Specially calibrated suspension settings		
Rear	Live axle four bar link with variable rate coil-springs on Boxed lower trailing arms, .94 in. stabilizer bar, Quadra Shock System with Saleen N2 Shocks and N2 Dampers		

BRAKES

Saleen ABS 4-Piston Calipers			
13.0 in. Grooved Disc (Front)	Optional		

WHEELS AND TIRES

Saleen Five Spoke Alloy Wheels			
18 in. x 9 in. Front	Standard		
18 in. x 9 in. Rear	Standard		
18 in. x 10 in. Rear	Optional		
High Performance Pirelli P7000			
P255/35 ZR-18 (Front)	Standard		
P265/35 ZR-18 (Rear)	Standard		
High Performance Pirelli P-Zero Upgrade			
P265/35 ZR-18 (Front)	Optional		
P295/35 ZR-18 (Rear)	Optional		